

DuRock Lo-Voc Sealer

Acrylic Sealer

PRODUCT DESCRIPTION

DuROCK LO-VOC Sealer is a solvent based sealer that penetrates the surface to create a durable surface that will resist all but the most caustic chemicals.

DuROCK LO-VOC Sealer is used for both interior and exterior applications. **DuROCK LO-VOC Sealer** give the surface a shiny look and enhance the colors of decorative concrete.

STORAGE & MIXING

DuROCK LO-VOC Sealer contains a combustible solvent and therefore **must be kept away from any ignition source or sources of heat at all times**. Only apply **DuROCK LO-VOC Sealer** in areas that are well ventilated or where there is access to ventilation.

Store **DuROCK LO-VOC Sealer** above 10°C (50°F) and below 30°C (86°F), off the ground and in a dry place away from direct sunlight. Employ temporary protection measures as needed. Under no circumstances shall **DuROCK LO-VOC Sealer** be permitted to freeze. Protect material from excessive evaporation during dry weather.

Prior to use mix using a stainless steel or corrosion resistant mixing blade and power drill ensuring not to induce air into the product. Do not add water.

APPLICATION & COVERAGE

Old concrete surfaces must be solid with any holes, cracks or spalled areas patched or filled. Surfaces must be dry, clean and free of any dirt, grease, oil or other substances that could affect adhesion. Non-porous surfaces should be etched with muriatic acid, rinsed and allowed to completely dry.

Surface and ambient temperatures must be at least 10°C (50°F) a minimum of 24 hours, and must remain so until **DuROCK LO-VOC Sealer** has cured. Do not apply to a frozen base or a base containing frost. Wherever possible, avoid application in direct sunlight. Mask off all areas adjacent to those upon which **DuROCK LO-VOC Sealer** will be applied.

Apply a minimum of two coats of **DuROCK LO-VOC Sealer** to the surface. For roller application a medium pile roller is recommended. Using a medium pile roller, dip into the pail of **DuROCK LO-VOC Sealer** and apply it to the surface to be coated. The first coat should be applied thinly allowing for sufficient time for curing to occur before applying the remaining coats. Work the **DuROCK LO-VOC Sealer** with several passes of the roller and spread it to an even coat. Repeat this process until uniform coverage is achieved.

DuROCK LO-VOC Sealer is available in 19 L pails (19kg/pail) with a coverage rate of approximately 1000ft² per pail, depending on surface porosity. Actual coverage depends on jobsite conditions and other factors.

TECHNICAL DATA

Technical data available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.