

Jewel Stone Plus Binder

Cement Additive

PRODUCT DESCRIPTION

Jewel Stone Plus Binder is a water-based, acrylic polymer that is used primarily as an additive for **Jewel Stone Plus** dry mix. The addition of **Jewel Stone Plus Binder** increases the flexibility of the products it is added to. With the use of **Jewel Stone Plus Binder** the overall bonding, compressive, flexural, tensile, and cohesive strength any cement parge is increased.

Jewel Stone Plus Binder can be mixed with **Jewel Stone Plus** dry mix to form a highly flexible textured coating to be used over interior or exterior walls or floors. When mixed with **Fine Parge** (a multi-purpose cement parge) and applied over expanded polystyrene, **Jewel Stone Plus Binder** forms a highly flexible base coat over which an acrylic finish coat is applied. **Jewel Stone Plus Binder** is available in 5 US gallon (19L) pails.

STORAGE & MIXING

Store **Jewel Stone Plus Binder** at temperatures above 5°C (41°F) and below 40°C (104°F), and off the ground in a dry place away from direct sunlight. **Under no circumstances shall Jewel Stone Plus Binder be permitted to freeze.** Thoroughly remix **Jewel Stone Plus Binder** before each use. Clean tools often.

For complete mixing instructions please refer to **Jewel Stone Plus** decorative floor finish datasheet.

APPLICATION & COVERAGE

When mixed with **Jewel Stone Plus Binder**, one 50 lb (22.7 kg) bag of **Jewel Stone Plus** dry mix covers approximately 50 ft² (4.6 m²) at 1/8 in (3.2 mm) wet film thickness.

For complete application instructions please refer to Jewel Stone Plus decorative floor finish datasheet.

TECHNICAL DATA

Available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.