



* Wood Sheathing

DuROCK Roller Bear or Polar Bear Moisture Barrier

DuROCK Polar Bear Moisture Barrier/Adhesive

DuROCK PUCCS Insulation with 10mm Geometrically Defined Drainage Cavity (GDDC)

DuROCK Fibre Mesh embedded in DuROCK Prep Coat

DuROCK Finish Coat

Min. slope 1:2

* EIFS Moulding

DuROCK Adhesive

Wrap insulation edge with reinforcing mesh, terminate base coat at drainage track

* Optional Backer Rod and Sealant (vented)

DuROCK Uni-Flash self-flashing drainage track

Sealant under Uni-Flash

* Self-Adhering Transition Membrane wrapped into rough opening

* Window

(* by others)

PUCCS-LRRC
(FOR LOW-RISE RESIDENTIAL CONSTRUCTION)

DRAWING TITLE:
**WINDOW HEADER WITH
DuROCK PVC UNI-FLASH**

This detail complements the corresponding system specification and illustrates the system configuration for the depicted construction. Visit www.durock.com for the latest revisions and contact DuROCK for project-specific details to suit conditions other than those depicted. DuROCK assumes no liability for the architecture, design, engineering, or workmanship of any project.

DuROCK
Alfacing International Limited
101-B ROYTEC ROAD
WOODBIDGE, ONTARIO
TEL : (905) 856-0133, FAX : (905) 856-9654
www.durock.com
ARCHITECTURAL FINISHING SYSTEMS

LAST REVISION:	MAR 2017
ISSUED:	MAR 2007
DRAWN BY:	RIZ
SCALE:	NTS
PUCCS-LRRC	
D01	