

* Wood Sheathing

DuROCK Roller Bear or Polar Bear Moisture Barrier

DuROCK Polar Bear Moisture Barrier/Adhesive

DuROCK PUCCS, EPS Insulation Board with 10mm (GDDC) Geometrically Defined Drainage Cavity

DuROCK Reinforcing Mesh embedded in DuROCK Prep Coat

DuROCK Finish Coat

Min slope 1:2

* Decorative moulding

Wrap insulation edge with reinforcing mesh, terminate base coat at drainage track

* Optional Backer Rod and Sealant (vented)

DuROCK Uni-Flash self-flashing drainage track

* Window

DuROCK Polar Bear applied continuously inside the opening extending a minimum of 50mm (2") onto the sheathing

(* by others)

DuROCK SYSTEM:

PUCCS-LLRC

(FOR LOW-RISE RESIDENTIAL CONSTRUCTION)

DRAWING TITLE:

WINDOW HEADER WITH DuROCK PVC UNI-FLASH

This detail complements the corresponding system specification and illustrates the system configuration for the depicted construction. Visit www.durock.com for the latest revisions and contact DuROCK for project-specific details to suit conditions other than those depicted. DuROCK assumes no liability for the architecture, design, engineering, or workmanship of any project.



Alfacing International Limited

101-B ROYTEC ROAD
WOODBRIDGE, ONTARIO
TEL : (905) 856-0133, FAX : (905) 856-9654
www.durock.com

ARCHITECTURAL FINISHING SYSTEMS

LAST REVISION: MAR 2020

ISSUED: MAR 2007

DRAWN: RIZ

SCALE: NTS

PUCCS-LLRC
D-01