



- * Wood Sheathing
- DuROCK Roller Bear or Polar Bear Moisture Barrier
- DuROCK Polar Bear Moisture Barrier/Adhesive
- DuROCK PUCCS, EPS Insulation Board with 10mm (GDDC) Geometrically Defined Drainage Cavity
- DuROCK Reinforcing Mesh embedded in DuROCK Prep Coat
- DuROCK Finish Coat

- * Decorative moulding
- * Self-Adhering Transition Membrane lapped onto metal flashing
- Wrap insulation edge with reinforcing mesh, terminate base coat at GDDC

- * Backer rod and Sealant (vented)
- * Metal Flashing
- * Sealant under flashing drip edge (optional)
- * Window

DuROCK Polar Bear applied continuously inside the opening extending a minimum of 50mm (2") onto the sheathing

(* by others)

DuROCK SYSTEM:
PUCCS-LLRC
 (FOR LOW-RISE RESIDENTIAL CONSTRUCTION)

DRAWING TITLE:
WINDOW HEADER WITH METAL FLASHING

This detail complements the corresponding system specification and illustrates the system configuration for the depicted construction. Visit www.durock.com for the latest revisions and contact DuROCK for project-specific details to suit conditions other than those depicted. DuROCK assumes no liability for the architecture, design, engineering, or workmanship of any project.

DuROCK
 Alfacing International Limited
 101-B ROYTEC ROAD
 WOODBRIDGE, ONTARIO
 TEL : (905) 856-0133, FAX : (905) 856-9654
www.durock.com
 ARCHITECTURAL FINISHING SYSTEMS

LAST REVISE: JAN 2019
 ISSUED: MAR 2007
 DRAWN: RIZ
 SCALE: NTS

PUCCS-LLRC
D-02