



Glaze

Acrylic Sealer

PRODUCT DESCRIPTION

DuROCK Glaze is an acrylic glaze for interior applications. With this product, an infinite variety of designs and effects can be achieved. It is ideal for use over a variety of substrates including interior walls. The acrylic polymer used provides excellent resistance to water blushing or water whitening with excellent adhesion to several substrates. This polymer also exhibits excellent dirt pick-up resistance. There is the added benefit of film hardness, and good chemical and stain resistance.

STORAGE & MIXING

Store **DuROCK Glaze** above 10°C (50°F) and below 30°C (86°F), off the ground and in a dry place away from direct sunlight. Employ temporary protection measures as needed. Under no circumstances shall **DuROCK Glaze** be permitted to freeze. Protect material from excessive evaporation during dry weather.

Prior to use mix using a stainless steel or corrosion resistant mixing blade and power drill ensuring not to induce air into the product. Do not add water.

APPLICATION & COVERAGE

Substrate must be clean, dry, and free of loose material, wax, grease or any other contaminants. It is recommended that hard, glossy areas should be dulled with a fine sandpaper to improve adhesion. Surface and ambient temperatures must be at least 10°C (50°F) for a minimum of 24 hours, and must remain so until the **Glaze** has cured. Mask off all areas adjacent to those upon which **DuROCK Glaze** will be applied.

DuROCK Glaze can be applied using a variety of specialty finish tools or by brush. Using the appropriate tool and technique apply the glaze over a properly prepared surface. Depending on the technique, work in small sections blending from section to section. Some techniques include the following:

1. Sponging On/Sponging Off: Using a water-dampened sponge, work the glaze into the substrate surface in a random pattern. Using a circular motion apply or remove the glaze to achieve desired finish.
2. Ragging On/Ragging Off: Using a lint-free rag or soft cloth that is water dampened, apply or remove the glaze to achieve desired finish.
3. Colour-washing: Using a brush apply various coloured glazes to achieve a textured finish.

DuROCK Glaze is available in 19 L (4.18 gallons) pails and 5 L (1 gallon) pails. The average rate of coverage per pail is 1000ft² per 19 L pail (19 kg/pail). Actual coverage depends on substrate conditions as well as jobsite conditions.

TECHNICAL DATA

Technical data available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.