

# MATERIAL SAFETY DATA SHEET DUROCK ALFACING INTERNATIONAL LTD.

# 1. Chemical Product and Company Identification

Chemical Name: Faux Grip MSDS Date: March 2016

Company Identification
DuROCK Alfacing International Ltd.
101B Roytec Rd

Woodbridge, On

L4L 8A9

Emergency Telephone Numbers Health Emergency: 905-856-0133 Spill Emergency: 905-856-0133

#### 2. Hazardous Identification

Primary Routes of Exposure

X Inhalation Skin Absorption X Eye Contact Ingestion X Skin Contact

## Effects of Acute Exposure to Product

May cause respiratory tract irritation and central nervous system (CNS) depression at high concentrations. Can be absorbed through intact skin. May cause eye irritation, redness and pain. Can cause respiratory failure, cardiovascular collapse, pulmonary edema, and kidney failure if ingested.

## Other Health Effects

Survival of CNS depression may be followed by cardiopulmonary failure, which is initiated by the onset of coma, and is characterized by quick, shallow breathing, excessively fast heartbeat, mild hypertension and cyanosis. In severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement and possible death may occur. Survival of cardiopulmonary failure may be followed by kidney damage, which may range from a mild increase in blood urea nitrogen to complete kidney failure, and possible death.

## 3. Composition/Information on Ingredients

<u>Chemical Name</u> Propylene Glycol	CAS REG NO. 000057-55-6	Weight (%) 0.2-0.5	TLV(mg/m³) Not listed	LC <sub>50</sub> /LD <sub>50</sub> LC <sub>50</sub> (oral,rat)>3000mg/kg
Fropylerie Glycol	000037-33-0	0.2-0.5	Not listed	LD <sub>50</sub> (dermal,rabbit)> 5000mg/kg
Ester Alcohol	25265-77-4	0.2-0.4	Not listed	LC <sub>50</sub> (oral,rat)=6517mg/kg LD <sub>50</sub> (dermal,rabbit)> 15200mg/kg
E Glycol Ether EB	111-76-2	0.2-0.4	Not listed	LD <sub>50</sub> (rat)>470mg/kg LD <sub>50</sub> (rabbit)>220mg/kg
Acrylic/Styrene Emulsion	N/A	20-25	N/A	N/A
Fiber	N/A	0.5-1	N/A	N/A
Mica	12001-26-2	3-5	N/A	N/A
Silica Sand	N/A	50-55	N/A	N/A
Calcium Carbonate	N/A	10-15	N/A	N/A
In Can Preservative	N/A	0.2-0.3	N/A	N/A

DUROCK ALFACING INTERNATIONAL LTD. 101B ROYTEC RD WOODBRIDGE, ON L4L 8A9 PRODUCT: FAUX GRIP MSDS DATE: MARCH 2016

#### 4. First Aid Measures

#### Inhalation

Move victim to fresh air. Give artificial respiration only if breathing has stopped. Give cardiopulmonary resuscitation (CPR) if there is no breathing and no pulse. Obtain medical attention immediately.

#### **Eye Contact**

Immediately flush eyes with running water for a minimum of 20 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention immediately.

#### Skin Contact

Flush skin with running water and wash affected areas thoroughly with soap and water. Start flushing while removing contaminated clothing. Obtain medical attention immediately.

#### Ingestion

If victim is alert and not convulsing, give  $\frac{1}{2}$  to 1 glass of water to dilute the material. DO NOT INDUCE VOMITING. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomitus, rinse mouth and administer more water. Obtain medical attention immediately.

General information: Treat symptomatically

## 5. Fire Fighting Measures

Flash Point: N/A

Auto-Ignition Temperature: N/A Lower Explosive Limit: N/A Upper Explosive Limit: N/A Unusual Hazards: N/A Extinguishing Agents: N/A

## 7. Handling and Storage

#### **Storage Conditions**

Storage temperature should not exceed 40°C (104°F) or fall below 4°C (40°F).

#### Handling Procedures

N/A

#### 8. Personal Protection

## Respiratory Protection

NIOSH/MSHA approved respirator if required.

#### Hand Protection

Use gloves and protective clothing made of material which has been found by user to be impervious under conditions of use.

DUROCK ALFACING INTERNATIONAL LTD. 101B ROYTEC RD WOODBRIDGE, ON L4L 8A9 PRODUCT: FAUX GRIP MSDS DATE: MARCH 2016

#### 8. Personal Protection cont.

## **Eye Protection**

Safety glasses with side shields are recommended to prevent eye contact.

#### Engineering Controls (Ventilation)

Use local exhaust or general ventilation to keep the airborne concentrations below the applicable exposure limits.

## 9. Physical and Chemical Properties

Colour: Milky white State: Liquid

Odour Characteristics: Ammonia odour

PH: N/A Viscosity: N/A

Specific Gravity (Water=1): 1-1.2 Solubility in Water: Miscible Percent Volatility: N/A

Evaporation Rate (Bac\_1): >1.0

## 10. Stability and Reactivity

Instability Hazardous Decomposition

Chemically stable Not available

<u>Hazardous Polymerization</u> <u>Incompatibility</u>
Not available

Not available

## 11. Toxicological Information

Acute Data: N/A
Oral LD50 – rat: N/A
Dermal LD50 – rabbit: N/A
Skin irritation – rabbit: N/A
Eye irritation – rabbit: N/A

## 14. Transport Information

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

DUROCK ALFACING INTERNATIONAL LTD. 101B ROYTEC RD WOODBRIDGE, ON L4L 8A9 PRODUCT: FAUX GRIP MSDS DATE: MARCH 2016

# 16. Other Information

MSDS prepared by: DuROCK Alfacing International Limited

101B Roytec Rd Woodbridge, On L4L 8A9

Supplier/Manufacturer: DuROCK Alfacing International Limited

101B Roytec Rd Woodbridge, On

L4L 8A9