

DuROCK Top Coat Sealer 18% solids for concrete and masonry

PRODUCT DESCRIPTION

Top Coat Sealer is xylene/acrylic based sealer that penetrates the surface to create a durable surface that will resist all but the most caustic chemicals. **Top Coat Sealer** is used for both interior and exterior applications. Top Coat Sealer gives the surface a shiny look and enhances the colours of decorative concrete.

STORAGE & MIXING

Top Coat Sealer contains a combustible solvent and therefore **must be kept away from any ignition source or sources of heat at all times**. Only apply **Top Coat Sealer** in areas that are well ventilated or where there is access to ventilation.

Store **Top Coat Sealer** above 10°C (50°F) and below 30°C (86°F). Store buckets off the ground and in a dry place away from direct sunlight. Employ temporary protection measures as needed. Under no circumstances shall **Top Coat Sealer** be permitted to freeze. Protect material from excessive evaporation during dry weather.

Prior to use mix using a stainless steel or corrosion resistant mixing blade and power drill ensuring not to induce air into the product. Do not add water.

APPLICATION & COVERAGE

Old concrete surfaces must be solid with any holes, cracks or spalled areas patched or filled. Surfaces must be dry, clean and free of any dirt, grease, oil or other substances that could affect adhesion. Non-porous surfaces should be etched with muriatic acid, rinsed and allowed to completely dry.

Surface and ambient temperatures must be at least 10°C (50°F) a minimum of 24 hours, and must remain so until **Top Coat Sealer** has cured. Do not apply to a frozen base or a base containing frost. Wherever possible, avoid application in direct sunlight. Mask off all areas adjacent to those upon which **Top Coat Sealer** will be applied.

Apply a minimum of two coats of **Top Coat Sealer** to the surface. For roller application a medium pile roller is recommended. Using a medium pile roller, dip into the pail of **Top Coat Sealer** and apply it to the surface to be coated. The first coat should be applied thinly allowing for sufficient time for curing to occur before applying the remaining coats. Work the **Top Coat Sealer** with several passes of the roller and spread it to an even coat. Repeat this process until uniform coverage is achieved.

The average rate of coverage per pail is 1000ft² per pail, depending on surface porosity. Actual coverage depends on jobsite conditions and other factors.

TECHNICAL DATA

Technical data is available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.