

DuROCK PUCCS, EPS Insulation Board with 10mm (GDDC) Geometrically Defined Drainage Cavity

Wrap insulation edge with reinforcing mesh, terminate base coat at drainage track

DuROCK Uni-Track drainage track with lip

Wooden Deck (by others)

Minimum 50mm (2")

Self-Adhering Transition Membrane (by others)

Metal Flashing (by others)
Sealant under flashing drip edge (optional)

Wrap insulation edge with mesh-reinforced base coat

DuROCK Polar Bear Moisture Barrier/Adhesive

DuROCK Roller Bear or Polar Bear Moisture Barrier

Wood Sheathing (by others)

DuROCK SYSTEM:

PUCCS-LRRC

(FOR LOW-RISE AND RESIDENTIAL CONSTRUCTION)

DRAWING TITLE:

TERMINATION AT BALCONY/DECK

This detail complements the corresponding system specification and illustrates the system configuration for the depicted construction. Visit www.durock.com for the latest revisions and contact DuROCK for project-specific details to suit conditions other than those depicted. DuROCK assumes no liability for the architecture, design, engineering, or workmanship of any project.



Alfacing International Limited

101-B ROYTEC ROAD
WOODBRIDGE, ONTARIO
TEL : (905) 856-0133, FAX : (905) 856-9654
www.durock.com

ARCHITECTURAL FINISHING SYSTEMS

LAST REVISE: MAR 2024

ISSUED: MAR 2007

DRAWN: RIZ

SCALE: NTS

PUCCS-LLRC

D-06