

DuROCK Woodpecker Deterrent (WPD)

PRODUCT DESCRIPTION

DuROCK WPD is a premixed, water-based, 100% acrylic coating available in unlimited colours. **DuROCK WPD** is a breathable, water-repelling, dirt pick-up resistant (DPR), ultraviolet resistant finish consisting of fine fillers, pigment, resin and other additives formulated for use as a top coat for DuROCK EIFS. **DuROCK WPD** incorporates an ingredient that acts as a safe, effective deterrent to woodpeckers. The ingredient used has a repulsive taste that both humans and animals are sensitive to. This ingredient is not harmful and is found in many consumer products.

STORAGE & MIXING

Store **DuROCK WPD** above 4°C (40°F), below 40°C (104°F), off the ground, and in a dry place away from direct sunlight. Under no circumstances shall **DuROCK WPD** be permitted to freeze.

Using a stainless steel or corrosion resistant mixing blade and power drill, mix at 400 – 500 rpm, ensuring not to induce air into the product. Mix product until a uniform consistency is attained. Up to 250mL (8oz) of potable water can be added to a full pail of finish coat to adjust workability in hot temperature conditions. Accelerators and other additives are prohibited.

APPLICATION & COVERAGE

Substrate must be clean, dry, and free of cracks or loose material. Surface and ambient temperatures must be at least 4°C (40°F) for a minimum of 24 hours, and must remain so until **DuROCK WPD** has dried. The surface shall be dry and firm to the touch before being exposed to ambient conditions. Do not apply **DuROCK WPD** in direct sunlight at temperatures exceeding 30°C (86°F) and protect from winds exceeding 25 km/hr (15 mph) as well as precipitation for at least 24 hours.

Apply **DuROCK WPD** with a medium pile roller until uniform coverage is achieved. Do not use a paint tray. Maintain a wet edge for colour uniformity. Work **DuROCK WPD** with several passes of the roller until a uniform coat is achieved. The final passes of the roller should be consistent in direction and applied pressure. The application must be continuous across wall areas, starting and ending at natural breaks in the surface.

When spray applying, only use manufacturer approved spray gun and air compressor. Apply a light coat by moving the spray gun in a smooth and steady motion so as to avoid excessive buildup. Repeat the process until the coverage is uniform throughout. Protect adjacent areas when applying any coating.

Clean all tools and equipment with water immediately after use.

DuROCK WPD is available in 19 L (5 gallon US) pails. The coverage per 19L pail is 700ft² (65m²).

PRECAUTIONS

This product has a very unpleasant taste if ingested. Wear disposable gloves when using and handle carefully. Avoid touching anything else before clean-up. Clean up by washing hands with soap and water. Make sure all other surfaces and surrounding area that may have been exposed are cleaned using soap and water.