DuROCK Woodpecker Deterrent (WPD)

PRODUCT DESCRIPTION

DuROCK WPD is a premixed, water-based, 100% acrylic coating available in unlimited colours. **DuROCK WPD** is a breathable, water-repelling, dirt pick-up resistant (DPR), ultraviolet resistant finish consisting of fine fillers, pigment, resin and other additives. **DuROCK WPD** is available as a stand-alone topcoat that can be applied directly over a standard DuROCK finish, and **DuROCK WPD** is available as an additive that is mixed directly into standard DuROCK finishes. **DuROCK WPD** incorporates an ingredient that acts as a safe, effective deterrent to woodpeckers. While the active ingredient in **DuROCK WPD** has a repulsive and bitter taste, it is not harmful, as it is found in many consumer products.

STORAGE & MIXING

Store **DuROCK WPD** above 4°C (40°F), below 40°C (104°F), off the ground, and in a dry place away from direct sunlight. Under no circumstances shall product in pails be permitted to freeze.

Using a stainless steel or corrosion resistant mixing blade and power drill, mix at 400 – 500 rpm, ensuring not to induce air into the product. Mix the product until a uniform consistency is attained. Up to 250mL (8oz) of potable water can be added to a full pail of finish coat to adjust workability in hot temperature conditions. Accelerators and other additives are prohibited.

APPLICATION & COVERAGE

Substrate must be clean, dry, and free of cracks or loose material. Surface and ambient temperatures must be at least 4°C (40°F) for a minimum of 24 hours and must remain so until **DuROCK WPD** has dried. The surface shall be dry and firm to touch before being exposed to ambient conditions. Do not apply **DuROCK WPD** in direct sunlight at temperatures exceeding 30°C (86°F) and protect from winds exceeding 25 km/hr (15 mph) as well as precipitation for at least 24 hours.

When used as a stand-alone topcoat, apply **DuROCK WPD** in accordance with the data sheet for DuROCK Roller Finishes. Coverage is 700 sq ft (65 sq m) per 19 L (5-gallon US) pail.

When used as an additive in standard DuROCK finishes, apply the finish in accordance with the data sheet for the applicable texture. Coverage varies by texture.

PRECAUTIONS

This product has a very unpleasant taste if ingested. Handle **DuROCK WPD** with care and wear disposable gloves. Avoid touching anything else before cleaning up. Clean up by washing hands with soap and water. Make sure all other surfaces and surrounding area that may have been exposed are cleaned using soap and water.

© DuROCK Alfacing International Limited