

Pure Cement Binder

Cement Additive

PRODUCT DESCRIPTION

Pure Cement Binder is primarily used as an additive for **Jewel Stone** decorative floor finish. Pure Cement Binder is a 100% acrylic additive. The addition of **Pure Cement Binder** increases the overall bonding, compressive and cohesive strength to the substrate. **Pure Cement Binder** is a water-based acrylic-polymer.

When mixed with **Jewel Stone** dry mix, **Pure Cement Binder** forms a textured coating designed for use over interior or exterior, concrete or masonry, floors or walls. When mixed with **Fine Parge** and applied over concrete walls, **Pure Cement Binder** forms the base coat over which an acrylic finish coat is applied.

Refer to the appropriate data sheets for mixing instructions and application procedure. **Pure Cement Binder** is available in 5 gal US (19L) pails, 10 L containers, and 4 L containers.

STORAGE & MIXING

Store **Pure Cement Binder** at temperatures above 5°C (41°F) and below 40°C (104°F), and off the ground in a dry place away from direct sunlight. **Under no circumstances shall Pure Cement Binder be permitted to freeze.** Thoroughly remix **Pure Cement Binder** before each use. Clean tools often.

APPLICATION & COVERAGE

Jewel Stone can be applied in coats ranging from $\frac{1}{16}$ to $\frac{1}{2}$ in. (1.6 to 13 mm). When mixed with **Pure Cement Binder**, one 50 lb (22.7 kg) bag of **Jewel Stone** dry mix covers approximately 45ft² (4.2m²) at 3/16 inch (4.8 mm) thickness. **Jewel Stone** is available in 50 lb (22.7 kg) bags.

For complete application instructions please refer to **Jewel Stone** decorative floor finish specifications.

TECHNICAL DATA

Available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.